



## Jeep Grand Cherokee 2005-2010 catalytic converter



**Product codes:**

Reference: REG-JEEP01

EAN13: -



---

**Product features:**

Cartridge type: Standard  
Cartridge material: Metal  
Producer: AWG Polonez  
EURO standard: EURO 4  
Insert length: 100 mm  
Inlet diameter: 125 mm  
OE number: 115220234000  
Vehicle brand: Jeep  
Model: Grand Cherokee

**Product attributes:****Product description:**

The subject of the offer is the regeneration of catalytic converters involving the welding of new metal catalytic converter inserts into the original housings. The dimensions of the cartridge are optimally matched to this car in terms of diameter and length and are 125/100 mm. The emission standard of the cartridge is Euro 4 and the capacity is 500 cpsi. The manufacturer of the cartridges is a well-known Polish company Polonez AWG and the cartridges have all the necessary approvals and a 12-month warranty. We also have sports cartridges with increased throughput of 200-400 cpsi.

We do the regeneration in one day and send you back the catalytic converter ready for installation.

When sending a catalyst to us fill out the form :

<https://regeneracjakatalizatorow.pl/pl/content/6-regeneracja-katalizatorow>

Also, do not forget to remove the cause of faster wear of the cartridge, if its wear has occurred faster than standard the cause may be oil or fuel entering the exhaust system. If you have a gas installation, it also contributes to faster wear of the original ceramic cartridges, which are not resistant to the higher temperature of gas combustion.

If you feel up to it, you can also replace the cartridges yourself, which you can buy from the link below:

[https://regeneracjakatalizatorow.pl/pl/universalne/390-2247-wklad-katalizatora-benzyna-awg.html#/37-dlugosc\\_wkladu-100\\_mm/50-srednica\\_wkladu-125\\_mm/57-norma\\_euro-euro\\_4/64-przepustowosc\\_cpsi-500STANANDARD-E6/130/100](https://regeneracjakatalizatorow.pl/pl/universalne/390-2247-wklad-katalizatora-benzyna-awg.html#/37-dlugosc_wkladu-100_mm/50-srednica_wkladu-125_mm/57-norma_euro-euro_4/64-przepustowosc_cpsi-500STANANDARD-E6/130/100)

Cut the original housing, weld the insert from the inside and weld the housing. The insert should be installed in accordance with the arrow engraved on the insert housing, which indicates the direction of the flue gas flow.

Nr OE:

115220234000 / 448AB / 33467

